


| PART NO. | AIR SIDE PLUG |
|----------|---------------|
| FA14949  | NO            |
| KT14949  | YES           |

| RATINGS                   |                  |
|---------------------------|------------------|
| VOLTAGE:                  | 500V DC          |
| CURRENT:                  | 3.6 AMPS         |
| PRESSURE:                 | 1400 PSIG @ 20°C |
| TEMPERATURE WITHOUT PLUG: | -269°C TO 450°C  |
| TEMPERATURE WITH PLUG:    | -65°C TO 165°C   |

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

THREE DOUBLE ENDED BNC

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)

**SST**

**SOLID SEALING TECHNOLOGY, INC.**

| REV. | APP'D | DATE       | SCALE 1:1   | DIMENSIONS IN INCHES [mm] | DRAWN     | MH | 09/22/2006 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| B2   | JS    | 10/15/2012 | COBN0035-11 |                           | ENG APPR. | MH | 10/27/2006 |

PART NO. FA14949 REV. B

SALES DWG NO. FA14949SL REV. B2