

PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA14964	CHROMEL / ALUMEL	K
FA14964-02	IRON / CONSTANTAN	J
FA14964-03	TUNGSTEN / RHENIUM*	C
FA14964-04	CHROMEL / CONSTANTAN	E


RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

* TYPE C USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: TWO PAIR T/C SPADE TYPE
 BASEPLATE FEEDTHRU



REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	8/4/2009
A2	JS	09/24/2012	MPCLO119-0ST		ENG APPR.	MH	08/07/2009

PART NO. (SEE TABLE) REV. A

SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14964SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.