

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA14966	COPPER	55 AMPS
FA14966-03	NICKEL	16.5 AMPS
FA14966-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	20KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	250 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14966SL REV. A1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

HV FEEDTHRU

PART NO. FA14966 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	05/18/2015
A1	JF	05/18/2015	FTCL0240-11		ENG APPR.	JF	05/18/2015

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**