



PLUGS SOLD SEPARATELY:  
 - VACUUM SIDE PEEK PLUG FA13604  
 - AIR SIDE PLUG KT14877

PERFORMANCE SPECIFICATIONS	
VOLTAGE	500 V DC
CURRENT	5 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE	-25°C TO 205°C

\*FOR INTERNAL PRESSURE 5 TO 100 PSIG  
 AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL  THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				 THIRD ANGLE PROJECTION		TITLE  15 PIN SUB-D CONNECTOR			 <b>SOLID SEALING</b> TECHNOLOGY	
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	02/28/2008	PART NO. FA14980 REV. B	WWW.SOLIDSEALING.COM	
B1	CW	4/14/2022	MPCL0121-01		ENG APPR.	MH	02/28/2008		SALES DWG NO. FA14980SL REV. B1	

***DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.***