



PART NO.	CONDUCTOR MATERIAL	CURRENT	AIR SIDE PLUG
FA15008	NICKEL	16 AMPS	NO
KT15008	NICKEL	16 AMPS	YES
FA15008-02	MOLYBDENUM	23 AMPS	NO
KT15008-02	MOLYBDENUM	23 AMPS	YES

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
VOLTAGE:	700V DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE WITHOUT PLUG:	-25°C TO 205°C
TEMPERATURE WITH PLUG:	-25°C TO 125°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA15008SL REV. A3

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]
A3	JS	11/26/2012	MPDP0026-3ST	

THIRD ANGLE PROJECTION		
DRAWN	MH	12/12/2006
ENG APPR.	MH	12/12/2006

TITLE:	FOUR PIN CONNECTOR
PART NO. (SEE TABLE) REV. A	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.