



FREQUENCY	CURRENT
100 KHz	300 AMPS
300 KHz	250 AMPS
450 KHz	200 AMPS
13.56 MHz	100 AMPS

RATINGS	
VOLTAGE:	14KV DC
FREQUENCY:	SEE TABLE AT LEFT
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE:	-55°C TO 350°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA15073SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

RF FEEDTHROUGH

PART NO. FA15073 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	02/13/2007
A2	JS	05/24/2013	FTST0072-11		ENG APPR.	MH	02/13/2007

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.