



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA15306	COPPER	330 AMPS
FA15306-03	NICKEL	98 AMPS
FA15306-04	304 STN STL	21 AMPS

RATINGS	
VOLTAGE	8KV DC
CURRENT	SEE TABLE AT LEFT
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE	-269°C TO 450°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA15306SL REV. A4

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

8KV FEEDTHRU

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	02/01/2008
A4	JS	05/24/2013	FTCL0079-0ST		ENG APPR.	MH	02/01/2008

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.