

| RATINGS | |
|--------------|-----------------|
| VOLTAGE: | 35KV DC |
| PRESSURE: | 350 PSIG @ 20°C |
| TEMPERATURE: | -55°C TO 450°C |

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA15380SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

VACUUM ISOLATOR

PART NO. FA15380 REV. A

| REV. | APP'D | DATE | SCALE 1:1 | DIMENSIONS IN INCHES [mm] | DRAWN | EB | 5/24/2006 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A2 | JF | 04/24/2014 | BRCL0017-02 | | ENG APPR. | MH | 10/27/2006 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.