



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA15433	NICKEL	16.5 AMPS
FA15433-02	COPPER	55 AMPS

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: SIX 5KV FEEDTHROUGHS		WWW.SOLIDSEALING.COM 		
REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]	DRAWN	OG	10/01/2007	PART NO. (SEE TABLE) REV. B		SOLID SEALING TECHNOLOGY, INC.	
B1	JF	08/28/2017	FTST0064-1ST		ENG APPR.	OG	10/01/2007			SALES DWG NO. FA15433SL REV. B1	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.