



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA15499	COPPER	330 AMPS
FA15499-03	NICKEL	98 AMPS
FA15499-04	304 STN STL	21 AMPS

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	8KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: 4 CONDUCTOR FEEDTHROUGH		WWW.SOLIDSEALING.COM 	
REV.	APP'D	DATE	SCALE 3:4	DIMENSIONS IN INCHES [mm]	DRAWN	JF	5/3/2017	PART NO. (SEE TABLE) REV. A		
A2	JF	5/4/2017	MPCLO064-2ST		ENG APPR.	JF	5/3/2017			SALES DWG NO. FA15499SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.