



PART NO.	AIR SIDE PLUG
FA15545	NO
KT15545	SIDE

PERFORMANCE SPECIFICATIONS	
VOLTAGE (DWV):	7KV DC
OPERATING VOLTAGE:	1.5 KV DC*
CURRENT:	7 AMPS
PRESSURE:	320 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 150°C**
TEMPERATURE WITH PLUG:	-65°C TO 150°C

\* BASED ON AIR SIDE PLUG

\*\*200°C SHORT TERM 150°C CONTINUOUS

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE HN CONNECTOR			
REV.	APP'D	DATE	SCALE 5:4	DIMENSIONS IN INCHES [mm]	DRAWN	JS	04/01/2010	PART NO. FA15545 REV. A	
A4	JF	02/24/2025	COHN004-11		ENG APPR.	MH	04/01/2010		
								SALES DWG NO. FA15545SL REV. A4	

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**