



PART NO.	AIR SIDE PLUG
FA15545	NO
KT15545	SIDE

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	7KV DC
CURRENT:	7 AMPS
PRESSURE:	320 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 150°C*
TEMPERATURE WITH PLUG:	-55°C TO 150°C

\*200°C SHORT TERM 150°C CONTINUOUS

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE <b>HN CONNECTOR</b>			
REV.	APP'D	DATE	SCALE 5:4	DIMENSIONS IN INCHES [mm]	DRAWN	JS	04/01/2010	PART NO. FA15545 REV. A WWW.SOLIDSEALING.COM	
A3	MH	1/20/2021	COHN0004-11		ENG APPR.	MH	04/01/2010		

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**