



PART NO.	CONDUCTOR MATERIAL	W WALL
FA15623	COPPER	.032 [0.81]
FA15623-02	304 STN STL	.035 [0.89]

PERFORMANCE SPECIFICATION	
VOLTAGE:	8KV DC
PRESSURE:	350 PSIG @ 20°C
TEMPERATURE:	-80°C TO 450°C*

*CALL SST TO CONFIRM LOWER TEMPERATURE USE

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 8KV FEEDTHROUGH			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	02/11/2015	PART NO. (SEE TABLE) REV. B	WWW.SOLIDSEALING.COM
B1	JF	11/09/2023	FTCL0087-1ST		ENG APPR.	JF	02/11/2015		SALES DWG NO. FA15623SL REV. B1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.