



PART NO.	CONDUCTOR MATERIAL	CURRENT	AIR SIDE PLUG
FA15628	NICKEL	16 AMPS	NO
KT15628	NICKEL	16 AMPS	YES
FA15628-02	MOLYBDENUM	23 AMPS	NO
KT15628-02	MOLYBDENUM	23 AMPS	YES

PERFORMANCE SPECIFICATIONS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
VOLTAGE:	700V DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	475 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-55°C TO 125°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE TWO PIN CONNECTOR			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	10/31/2006	PART NO. (SEE TABLE) REV. C	WWW.SOLIDSEALING.COM
C1	JF	12/1/2020	MPDP0024-1ST		ENG APPR.	MH	10/31/2006		SALES DWG NO. FA15628SL REV. C1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.