



+ CONDUCTOR LOCATIONS: A,C,E, G,J,L,N,R,T,V
 - CONDUCTOR LOCATIONS: B,D,F,H,K,M,P,S,U

PLUGS SOLD SEPARATELY:
 - AIR SIDE PLUG W/CRIMP CONTACTS: FA19649
 - VACUUM SIDE PEEK PLUG: FA19648

PERFORMANCE SPECIFICATIONS	
CONDUCTOR MATERIAL:	(+)CHROMEL / (-)ALUMEL
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 9 PAIR T/C TYPE K CONNECTOR				
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/8/2020	PART NO. FA15676 REV. A		WWW.SOLIDSEALING.COM
A1	JF	9/8/2020	MPCL0374-12SL		ENG APPR.	JF	9/8/2020			SALES DWG NO. FA15676SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.