



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA15729	COPPER	27 AMPS
FA15729-02	MOLYBDENUM	13.5 AMPS
FA15729-03	NICKEL 200	8.2 AMPS
FA15729-04	304 STN STL	1.8 AMPS

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	2KV DC
CURRENT:	SEE TABLE AT LEFT:
PRESSURE:	3500 PSIG @ 20°C
TEMPERATURE:	-80°C TO 450°C*

*CALL SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA15729SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

2 KV FEEDTHRU

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	6/10/2009
A2	JF	09/08/2017	FTCL0092-0ST		ENG APPR.	MH	06/10/2009

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.