


PLUGS SOLD SEPARATELY:  
 -VACUUM SIDE PEEK PLUG FA13604  
 -AIR SIDE PLUG KT14877

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	5 AMPS
PRESSURE:	0 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE  
 (2) 15 PIN SUB-D CONNECTORS



REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	06/03/2014
B2	MH	12/11/2025	MPCL0130-11		ENG APPR.	JF	06/03/2014

PART NO. FA15738 REV. B

WWW.SOLIDSEALING.COM  
 SALES DWG NO. FA15738SL REV. B2

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**