



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA15888	COPPER	30 AMPS	55 AMPS
FA15888-02	MOLYBDENUM	28 AMPS	28 AMPS
FA15888-03	NICKEL	16.5 AMPS	16.5 AMPS
FA15888-04	304 STN STL	3.6 AMPS	3.6 AMPS

PERFORMANCE SPECIFICATIONS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE	20KV DC	14KV DC
CURRENT	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	1500 PSIG @ 20°C	1500 PSIG @ 20°C
TEMPERATURE	-25°C TO 125°C	-269°C TO 450°C

MATES WITH POWERPLUG FP10883 & FP10883-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE FIVE 20KV FEEDTHRU			
REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]	DRAWN	MH	07/08/2008	PART NO. FA15888 REV. B WWW.SOLIDSEALING.COM	
B1	JF	4/12/2021	FTST0069-11		ENG APPR.	MH	07/08/2008		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.