


PART NO.	REMARKS	CONDUCTOR MATERIAL	CURRENT	VOLTAGE	AIR SIDE PLUG
FA16063	POWER	ALL ALUMEL	4.8 AMPS	700V DC	NO
KT16063	POWER	ALL ALUMEL	4.8 AMPS	700V DC	YES
FA16063-02	T/C	CHROMEL / ALUMEL	N/A	N/A	NO
KT16063-02	T/C	CHROMEL / ALUMEL	N/A	N/A	YES

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
VOLTAGE:	SEE TABLE AT LEFT
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-25°C TO 205°C
TEMPERATURE WITH PLUG:	-25°C TO 125°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR PIN BASEPLATE FEEDTHROUGH

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	11/09/2016
A1	JF	11/09/2016	MPDP0059-1ST		ENG APPR.	JF	11/09/2016

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA16063SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.