

RATINGS	
VOLTAGE:	1 KV DC
CURRENT:	3 AMPS
PRESSURE:	375 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PLUGS SOLD SEPARATELY:
 -VACUUM SIDE PEEK PLUG FA13463
 -AIR SIDE W/SOLDER CONTACTS FP14902
 -AIR SIDE W/CRIMP CONTACTS KT14380

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA16523SL REV. B1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

32 PIN CONNECTOR

PART NO. FA16523 REV. B

REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	3/21/2008
B1	JF	08/02/2017	MPCLO122-02SL		ENG APPR.	OG	04/08/2008

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.