

PLUGS SOLD SEPARATELY
 -AIR SIDE W/SOLDER CONTACTS FP14902
 -AIR SIDE W/CRIMP CONTACTS KT14380

RATINGS	
VOLTAGE:	1KV DC
CURRENT:	3 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA16531SL REV. A2

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:
32 PIN CONNECTOR

REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]
A2	JS	11/26/2012	MPCL0160-11SL	

DRAWN	JS	3/21/2008
ENG APPR.	MH	06/16/2008

PART NO. FA16531 REV. A

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.