



PERFORMANCE SPECIFICATIONS	
# OF CONDUCTORS	25
VOLTAGE:	600V AC / 850V DC
CURRENT:	5.5 AMPS PER CONDUCTOR
TEMPERATURE:	-55°C TO 200°C

CABLE IS AVAILABLE IN ANY LENGTH, PART NUMBER SUFFIX INDICATES LENGTH IN INCHES.

EXAMPLE: FA16655-038 IS A 38 INCH LONG CABLE.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 22 AWG RIBBON CABLE			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	5/19/2008	PART NO. FA16655 REV. A	
A3	JF	05/03/2024	AHDWR004-11		ENG APPR.	MH	07/11/2008		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.