



PART NO.	BACKSHELL INCLUDED
FA16705	NO
KT16705	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500 V DC
CURRENT:	5 AMPS
TEMPERATURE:	-269°C TO 200°C

REFER TO INSTRUCTION SHEET "NS13605" FOR PLUG ASSEMBLY INSTRUCTIONS.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE <b>37 PIN SUB D VACUUM PLUG</b>			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	3/23/2018	PART NO. FA16705 REV. A WWW.SOLIDSEALING.COM	
A4	JF	08/05/2022	MSME0028-11		ENG APPR.	MH	3/23/2018		

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**