


PART NO.	AIR SIDE PLUG
FA16764	NO
KT16764	YES

RATINGS	
VOLTAGE:	500V DC
CURRENT:	1.8 AMPS
PRESSURE:	1500 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR SMA CONNECTORS

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	06/13/2007
B1	JF	12/23/2013	COSA0019-12		ENG APPR.	MH	06/13/2007

PART NO. FA16764 REV. B

SALES DWG NO. FA16764SL REV. B1