



PART NO.	PLUGS INCLUDED
FA16933	NO
KT16933	YES

RATINGS	
VOLTAGE:	350V DC
CURRENT:	5 AMPS
PRESSURE:	400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUGS:	-269°C TO 450°C
TEMPERATURE WITH PLUGS:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				
REV.	APP'D	DATE	SCALE 5:4	DIMENSIONS IN INCHES [mm]
A2	JS	11/27/2012	MPCL0167-12	

THIRD ANGLE PROJECTION		
DRAWN	JS	7/25/2008
ENG APPR.	MH	08/27/2008

TITLE:	OCTAL CONNECTOR
PART NO. FA16933 REV. A	

WWW.SOLIDSEALING.COM

SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA16933SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.