

PART NO.	PLUGS INCLUDED
FA16933	NO
KT16933	YES

RATINGS	
VOLTAGE:	350V DC
CURRENT:	5 AMPS
PRESSURE:	400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUGS:	-269°C TO 450°C
TEMPERATURE WITH PLUGS:	-25°C TO 205°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA16933SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

OCTAL CONNECTOR

PART NO. FA16933 REV. A

REV.	APP'D	DATE	SCALE 5:4	DIMENSIONS IN INCHES [mm]	DRAWN	JS	7/25/2008
A2	JS	11/27/2012	MPCL0167-12		ENG APPR.	MH	08/27/2008