

PART NO.	PLUGS INCLUDED
FA16934	NO
KT16934	YES

RATINGS	
VOLTAGE:	350V DC
CURRENT:	5 AMPS
PRESSURE:	400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUGS:	-269°C TO 450°C
TEMPERATURE WITH PLUGS:	-25°C TO 205°C

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)




**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. FA16934SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

OCTAL CONNECTOR

PART NO. FA16934 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	7/25/2008
A2	JS	11/27/2012	MPCL0168-14		ENG APPR.	MH	08/27/2008

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**