



PERFORMANCE SPECIFICATIONS	
VOLTAGE:	8KV DC
CURRENT:	1000 AMPS
PRESSURE:	0 PSIG @ 20°C*
FLOW RATE:	0.3 GPM @ 15°C
TEMPERATURE:	-25°C TO 205°C

\*FOR INTERNAL PRESSURE 5 TO 100 PSIG  
AN OVERPRESSURE RING IS REQUIRED.

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</p>				<p>THIRD ANGLE PROJECTION</p> 		<p>TITLE</p> <p>8KV LIQUID COOLED FEEDTHRU</p>			 <p><b>SOLID SEALING</b> TECHNOLOGY</p>	
REV.	APP'D	DATE	SCALE 1:2	DIMENSIONS IN INCHES [mm]	DRAWN	JS	6/16/2008	PART NO. FA17004 REV. B	WWW.SOLIDSEALING.COM	
B2	JF	12/8/2020	FTCL0053-03		ENG APPR.	MH	07/08/2008		SALES DWG NO. FA17004SL REV. B2	

***DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.***