


PART NO.	PLUG INCLUDED
FA17155	NO
KT17155	YES

RATINGS	
VOLTAGE:	500V DC
CURRENT:	0.8 AMPS
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 350°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: DOUBLE ENDED 50 OHM  
SMA CONNECTOR



REV.	APP'D	DATE	SCALE 5:4	DIMENSIONS IN INCHES [mm]	DRAWN	JS	7/10/2009
A3	JS	10/22/2012	COSA0037-11		ENG APPR.	OG	07/15/2009

PART NO. FA17155 REV. A

**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. FA17155SL REV. A3

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**