



PART NO	CONDUCTOR MATERIAL	CURRENT
FA17430	COPPER	16 AMPS
FA17430-02	MOLYBDENUM	8.5 AMPS
FA17430-03	NICKEL 200	5 AMPS
FA17430-04	304 STN STL	1.1 AMPS

RATINGS	
VOLTAGE	1.5 KV DC
CURRENT	SEE TABLE AT LEFT
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE	-269°C TO 450°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA17430SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

EIGHT 1.5KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	03/24/2008
A2	JS	05/24/2013	MPDC0020-1ST		ENG APPR.	MH	03/24/2008

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.