


PART NO.	AIR SIDE PLUG
FA17447	NO
KT17447	YES

RATINGS	
VOLTAGE:	500V DC
CURRENT:	0.8 AMPS
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 350°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO DBL ENDED 50 OHM SMA

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)



**SOLID SEALING TECHNOLOGY, INC.**

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	08/19/2008
A2	JS	10/22/2012	COSA0028-11		ENG APPR.	MH	12/31/2008

PART NO. FA17447 REV. A

SALES DWG NO. FA17447SL REV. A2