



PART NO.	CONDUCTOR MATERIAL	CURRENT	AIR SIDE PLUG
FA17473	NICKEL	25 AMPS	NO
KT17473	NICKEL	25 AMPS	YES
FA17473-02	MOLYBDENUM	46 AMPS	NO
KT17473-02	MOLYBDENUM	46 AMPS	YES

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE LEFT
VOLTAGE:	700V DC
CURRENT:	SEE TABLE LEFT
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-55°C TO 125°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA17473SL REV. B1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR PIN CONNECTOR

PART NO. (SEE TABLE) REV. B

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	10/16/2007
B1	JS	11/26/2012	MPDP0071-1ST		ENG APPR.	MH	07/10/2008

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.