

PART NO.	AIR SIDE PLUG
FA17512	NO
KT17512	YES

RATINGS	
VOLTAGE	500V DC
CURRENT	0.8 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE WITHOUT PLUG	-25°C TO 205°C
TEMPERATURE WITH PLUG	-25°C TO 165°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG
AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA17512SL REV. A3

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE
SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO DOUBLE END 50 OHM SMAS

PART NO. FA17512 REV. A

REV.	APP'D	DATE	SCALE	DIMENSIONS IN	DRAWN	MH	03/07/2008
A3	JS	10/22/2012	COSA0020-11	INCHES [mm]	ENG APPR.	MH	03/07/2008