



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA17569	COPPER	55 AMPS
FA17569-02	MOLYBDENUM	28 AMPS
FA17569-03	NICKEL	16.5 AMPS
FA17569-04	304 STN STL	3.6 AMPS

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	14KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1500 PSIG @ 20°C
TEMPERATURE:	-260°C TO 230°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 14KV FEEDTHROUGH			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	02/15/2019	PART NO. (SEE TABLE) REV. B	WWW.SOLIDSEALING.COM
B2	JF	10/13/2021	FTST0092-0ST		ENG APPR.	JF	02/15/2019		SALES DWG NO. FA17569SL REV. B2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.