

MATES WITH POWERPLUG FA18788

PART NO.	COND MATERIAL	CURRENT** WITHOUT PLUG
FA17599	COPPER	100 AMPS
FA17599-02	MOLYBDENUM	50 AMPS
FA17599-03	NICKEL	30 AMPS
FA17599-04	304 STN STL	6.5 AMPS

PERFORMANCE SPECIFICATIONS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	10KV DC	5KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	1000 PSIG @ 20°C	1000 PSIG @ 20°C
TEMPERATURE:	-40°C TO 125°C*	-269°C TO 450°C

**SEE DOCUMENT "PRD-1303" UNDER TECHNICAL DATA FOR INFORMATION ON CURRENT PERFORMANCE OF MATING PLUG FA18788

*MAX TEMP OF MATING PLUG FA18788 DOES NOT TAKE IN CONSIDERATION HEAT RISE DUE TO OPERATING CURRENT

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA17599SL REV. A4

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:
10KV FEEDTHROUGH

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	03/10/2009
A4	JF	01/30/2019	FTST0003-4ST		ENG APPR.	MH	03/11/2009

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.