

PART NO.	AIR SIDE PLUG
FA17636	NO
KT17636	YES


RATINGS	
PIN/ SHIELD VOLTAGE:	500V DC
SHIELD/ GROUND VOLTAGE:	2.5KV DC
CURRENT:	1.8 AMPS
PRESSURE:	300 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-80°C TO 450°C*
TEMPERATURE WITH PLUG:	-65°C TO 165°C

* CALL SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE
 SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
 PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FLOATING SMA CONNECTOR



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 2.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	6/19/2008
B1	JF	12/23/2013	COSA0021-12		ENG APPR.	MH	07/11/2008

PART NO. FA17636 REV. B

SALES DWG NO. FA17636SL REV. B1