

PART NO.	AIR SIDE PLUG
FA17781	NO
KT17781	YES


RATINGS				
VOLTAGE:	500V DC			
CURRENT:	0.8 AMPS			
PRESSURE:	1400 PSIG @ 20°C			
TEMPERATURE WITHOUT PLUG:	-269°C TO 350°C			
TEMPERATURE WITH PLUG:	-65°C TO 165°C			

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

REV.	APP'D	DATE	SCALE 4:1	DIMENSIONS IN
A4	JS	11/19/2012	COBN0044-12	INCHES [mm]

THIRD ANGLE PROJECTION



	1			
N	DRAWN	MH	11/13/2007	
]	ENG APPR.	MH	11/13/2007	

TITLE:

DOUBLE ENDED 50 OHM BNC

PART NO. FA17781 REV. A



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA17781SL REV. A4