



PLUGS SOLD SEPARATELY:
 -VACUUM SIDE PEEK PLUG FA13462
 -AIR SIDE W/ SOLDER CONTACTS FP14901
 -AIR SIDE W/CRIMP CONTACTS KT14379

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	1KV DC
CURRENT:	3 AMPS
PRESSURE:	400 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 19 PIN CONNECTOR, 316L 2.75 CF			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	08/30/2006	PART NO. FA17905 REV. B WWW.SOLIDSEALING.COM	
B1	JF	3/22/2021	MPCL0102-11SL	ENG APPR.	JF	3/22/2021			

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.