



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA19154	304 STN STL	9 AMPS
FA19154-02	COPPER	135 AMPS

RATINGS	
VOLTAGE:	70KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	125 PSIG @ 20°C
TEMPERATURE:	-55°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: 70KV FEEDTHRU		WWW.SOLIDSEALING.COM 		
REV.	APP'D	DATE	SCALE 2:3	DIMENSIONS IN INCHES [mm]	DRAWN	JS	8/4/2008	PART NO. (SEE TABLE) REV. A		SOLID SEALING TECHNOLOGY, INC.	
A3	JS	05/24/2013	FC10122-2ST		ENG APPR.	MH	08/06/2008			SALES DWG NO. FA19154SL REV. A3	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.