



PLUGS SOLD SEPARATELY:

- VACUUM SIDE PEEK PLUG FA18064
- AIR SIDE W/SOLDER CONTACTS FP18062
- AIR SIDE W/CRIMP CONTACTS KT18063

RATINGS

VOLTAGE:	1 KV DC
CURRENT:	5 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG
AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: 3 PIN CONNECTOR		
REV.	APP'D	DATE	SCALE 3:2	DIMENSIONS IN INCHES [mm]	DRAWN	JS	8/26/2008	PART NO. FA19348 REV. B	SOLID SEALING TECHNOLOGY, INC. SALES DWG NO. FA19348SL REV. B1
B1	JF	08/09/2017	MPCL0243-12SL		ENG APPR.	MH	11/19/2008		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.