



PLUGS SOLD SEPARATELY:  
 - VACUUM SIDE PEEK PLUG FA18064  
 - AIR SIDE W/SOLDER CONTACTS FP18062  
 - AIR SIDE W/CRIMP CONTACTS KT18063

RATINGS	
VOLTAGE:	1 KV DC
CURRENT:	5 AMPS
PRESSURE:	550 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM

<div>PROPRIETARY AND CONFIDENTIAL</div> <div>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</div>					<div>THIRD ANGLE PROJECTION</div> <div></div>			<div>TITLE:</div> <div>3 PIN CONNECTOR</div>		<div></div> <div><b>SOLID SEALING TECHNOLOGY, INC.</b></div> <div>SALES DWG NO. FA19351SL REV. B1</div>
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	8/26/2008	PART NO. FA19351 REV. B		
B1	JF	08/09/2017	MPCL0244-12SL		ENG APPR.	MH	11/19/2008			

***DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.***