


PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE:	TYPE K
TEMPERATURE:	-269°C TO 200°C

CONTACT MATERIAL	LOCATIONS:
CHROMEL (+)	A,C,E,G,J,L,N,R,T,V,
ALUMEL (-)	B,D,F,H,K,M,P,S,U

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE
 TYPE K 9 PAIR VACUUM SIDE PLUG



REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/11/2020
A1	JF	9/11/2020	MSME0006-12		ENG APPR.	JF	9/11/2020

PART NO. FA19648 REV. A

WWW.SOLIDSEALING.COM

SALES DWG NO. FA19648SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.