



CRIMP CONTACT MATERIAL	LOCATIONS:
CHROMEL (+)	A,C,E,G,J,L,N,R,T,V
ALUMEL (-)	B,D,F,H,K,M,P,S,U

PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE:	TYPE K
TEMPERATURE:	-55°C TO 200°C

REFER TO INSTRUCTION SHEET "NS19649" FOR PLUG ASSEMBLY INSTRUCTIONS.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE TYPE K 9 PAIR AIR SIDE PLUG			
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	07/19/2011	PART NO. FA19649 REV. A	WWW.SOLIDSEALING.COM
A3	JF	06/30/2021	MSMM0018-13SL		ENG APPR.	JS	07/19/2011		SALES DWG NO. FA19649SL REV. A3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.