



CONTACT MATERIAL	LOCATIONS:
CHROMEL (+)	A,C,E,G,J,L,N,R,T,V
ALUMEL (-)	B,D,F,H,K,M,P,S,U

RATINGS	
THERMOCOUPLE	TYPE K
TEMPERATURE:	-55°C TO 200°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: <b>TYPE K 9 PAIR AIRSIDE PLUG</b>		<a href="http://WWW.SOLIDSEALING.COM">WWW.SOLIDSEALING.COM</a> 	
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	07/19/2011	<b>PART NO. FA19649 REV. A</b>		<b>SOLID SEALING TECHNOLOGY, INC.</b> SALES DWG NO. FA19649SL REV. A2
A2	JS	07/20/2011	MSMM0018-13SL		ENG APPR.	JS	07/19/2011			

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**