



CRIMP CONTACT MATERIAL	LOCATIONS:
CHROMEL (+)	A,C,E,G,J,L,N,R,T,V,X,Z,b,d,f,h
ALUMEL (-)	B,D,F,H,K,M,P,S,U,W,Y,a,c,e,g,j

PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE:	TYPE K
TEMPERATURE:	-55°C TO 200°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE TYPE K 16 PAIR AIR SIDE PLUG			
REV.	APP'D	DATE	SCALE 1.75:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/9/2020	PART NO. FA19814 REV. A	WWW.SOLIDSEALING.COM
A1	JF	9/9/2020	MSMM0019-13SL	ENG APPR.	JF	9/9/2020	SALES DWG NO. FA19814SL REV. A1		

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**