



CRIMP CONTACT MATERIAL	LOCATIONS:
CHROMEL (+)	A,C,E,G,J,L,N,R,T,V,X,Z,b,d,f,h
ALUMEL (-)	B,D,F,H,K,M,P,S,U,W,Y,a,c,e,g,j

PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE:	TYPE K
TEMPERATURE:	-55°C TO 200°C

REFER TO INSTRUCTION SHEET "NS19814" FOR PLUG ASSEMBLY INSTRUCTIONS.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE TYPE K 16 PAIR AIR SIDE PLUG			
REV.	APP'D	DATE	SCALE 1.75:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/9/2020	PART NO. FA19814 REV. A	WWW.SOLIDSEALING.COM
A2	JF	06/30/2021	MSMM0019-13SL		ENG APPR.	JF	9/9/2020		SALES DWG NO. FA19814SL REV. A2

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**