



PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE:	TYPE K
TEMPERATURE:	-200°C TO 200°C

CONTACT MATERIAL	LOCATIONS:
CHROMEL (+)	A,C,E,G,J,L,N,R,T,V,X,Z,b,d,f,h
ALUMEL (-)	B,D,F,H,K,M,P,S,U,W,Y,a,c,e,g,j

REFER TO INSTRUCTION SHEET "NS19815" FOR PLUG ASSEMBLY INSTRUCTIONS.

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</p>				<p>THIRD ANGLE PROJECTION</p> 		<p>TITLE</p> <p>TYPE K 16 PAIR VACUUM SIDE PLUG</p>			 <p>SOLID SEALING TECHNOLOGY</p>	
REV.	APP'D	DATE	SCALE 1.75:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/9/2020	PART NO. FA19815 REV. A	WWW.SOLIDSEALING.COM	
A3	JF	07/08/2021	MSME0007-02EX		ENG APPR.	JF	9/9/2020		SALES DWG NO. FA19815SL REV. A3	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.