

PART NO.	AIR SIDE PLUG INCLUDED
FA19889	NO
KT19889	YES

RATINGS	
PIN / SHIELD VOLTAGE:	500V DC
SHIELD / GROUND VOLTAGE:	2.5KV DC
CURRENT:	0.8 AMPS
PRESSURE:	300 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-80°C TO 450°C*
TEMPERATURE WITH PLUG:	-65°C TO 165°C

\*CALL SST TO CONFIRM LOWER TEMPERATURE USE

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)




**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. FA19889SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

DBL ENDED FLOATING 50 OHM BNC

PART NO. FA19889 REV. A

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	12/11/2008
A2	JS	10/15/2012	COBN0048-11		ENG APPR.	OG	12/11/2008

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**