


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA20134	COPPER	330 AMPS
FA20134-03	NICKEL	98 AMPS
FA20134-04	304 STN STL	21 AMPS

RATINGS	
VOLTAGE:	8KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

8KV FEEDTHROUGH

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	11/30/2010
A2	JS	05/24/2013	FC10044-7ST		ENG APPR.	JS	11/30/2010

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA20134SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.