


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA20448	COPPER	27 AMPS
FA20448-02	MOLYBDENUM	13.5 AMPS
FA20448-03	NICKEL	8.2 AMPS
FA20448-04	304 STN STL	1.8 AMPS

PERFORMANCE SPECIFICATIONS	
VOLTAGE	3KV DC
CURRENT	SEE TABLE AT LEFT
TEMPERATURE	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 3KV FEEDTHRUS

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	02/20/2009
B1	JF	12/14/2017	MPCL0277-1ST		ENG APPR.	MH	02/20/2009

PART NO. (SEE TABLE) REV. B

SALES DWG NO. FA20448SL REV. B1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.